

	LIFORNIA PLUME	SING	COI	DE (B	3A5		OFF	UPC)			
SYM	FIXTURE TYPE	SEMER	VENT	COLD	HOT WATER	MIXED			TOTAL M.	DR. FIXT	TOTAL DE
WC	ADA TOILET*	3"	2"	1"	Х	-	2	40,30,20,15,10	70	4	8
LAV	HAND SINK*	1 1/4"	1 1/2"	X	X	1/2"	2	1	2	1	2
S-1	UTILITY/MOP SINK	2"	1 1/2"	1/2"	×	1/2"	1	3	3	3	3
DF-1	DRINKING FOUNTAIN*	1 1/2"	1 1/2"	1/2"	×	-	3	.5	1.5	.5	1.5
HB-1	WALL HYDRANT ANTI-FREEZE	X	X	3/4"	X	-	1	2.5	2.5	NA	NA
HB-2	WALL FAUCET	X	X	1/2"	X	-	1	1	1	NA	NA
FD-1	FLOOR DRAIN	3"	1 1/2"	Х	X	_	1	NA	NA	2	2
FD-2	FLOOR DRAIN (EMERGENCY)	3"	1 1/2"	X	Х	-	2	NA	NA	NA	NA
WH-2	WATER HEATER (INSTANT)*	×	X	3/8"c	3/8"c	3/8"c	1	NA	NA	NA	NA



SIOUX CHIEF (3" W/6" STRAINER)

## GENERAL PLUMBING NOTES:

- 1. ALL PIPE ( MATER, SEMER, VENT), JOINTS, AND MORK SHALL CONFORM TO 2022 CALIFORNIA PLUMBING CODE AND LOCAL CODES
- 2. CONTRACTOR TO CONFIRM LOCATIONS OF SEMER AND MATER TIE-INS.
- 3. CONTRACTOR TO SOLIDLY BRACE ALL PIPING TIGHT AGAINST WALLS. FOR LONG OR COMPLICATED RUNS, SECURELY MOUNT USING UNI-STRUT, IN STRAIGHT AND UNIFORM MANNER FOR FINISHED APPEARANCE. PIPING SHOWN IS DIAGRAMMATIC ONLY AND ACTUAL DESIGN TO BE BY CONTRACTOR.
- 4. CONTRACTOR MAY CHANGE PIPE SIZING IN FIELD TO PROVIDE ADEQUATE MATER PRESSURE TO ALL PLUMBING FIXTURES AS APPROVED BY INSPECTOR. ROMTEC BUILDINGS ARE DESIGNED TO HAVE 40-60 PSI WATER PRESSURE FOR THE PLUMBING FIXTURES. IF THE SITE HAS A PRESSURE OTHER THAN THIS, IT IS THE OWNER'S RESPONSIBILITY TO PROVIDE THE PRESSURE REDUCER OR BOOSTER PUMP NECESSARY.
- 5. CONTRACTOR TO DETERMINE AND PROVIDE MEANS FOR GRAVITY DRAINING ALL PLUMBING FIXTURES TO SEPTIC OR SANITARY SEMER SYSTEM. INSTALLER TO PROVIDE A CLEAN-OUT BENEATH ALL SINKS AND LAVATORY AS REQUIRED BY CODE.
- 6. CONTRACTOR TO DETERMINE AND PROVIDE MEANS FOR SUPPLYING MATER TO ALL PLUMBING FIXTURES AND INSTALL MATER SERVICE SHUTOFF VALVE: TYPICALLY LOCATED MITHIN THE MECHANICAL ROOM.
- 7. IF THE SITE REQUIRES AN ACCESSIBLE BACK FLOW PREVENTER AND/OR PRESSURE REDUCER OR BOOSTER PUMP IT IS THE OWNER'S RESPONSIBILITY TO PROVIDE.
- 8. WHEN INCLUDED. HOT MATER TANKS REQUIRE A TEMPERATURE AND PRESSURE RELIEF VALVE AND A DRAIN LINE TO THE EXTERIOR OF THE BUILDING PER 2022 CPC SECTIONS 608.4 \$ 608.5. CONTRACTOR TO PROVIDE = FURNISH & INSTALL TWO STRAPS TO THE NEAREST WALL, ONE STRAP AT TOP 1/3 OF TANK AND ONE STRAP AT BOTTOM 1/3 OF TANK, IN COMPLIANCE WITH 2022 CPC SECTION 507.2.
- 9. PLUMBING FIXTURES SHALL BE CERTIFIED BY THE CALIFORNIA ENERGY COMMISSION, SHALL COMPLY WITH 2022 CALIFORNIA PLUMBING CODE (CPC) SECTIONS 401.3 AND 403, AND SHALL COMPLY WITH 2022 CALIFORNIA GREEN BUILDING STANDARDS CODE (CGBSC) SECTION 5,303,3, FLUSHOMETERS ASSOCIATED MITH TOILETS SHALL USE NO MORE THAN 1.28 GALLONS PER FLUSH, FLUSHOMETERS ASSOCIATED MITH URINALS USE NO MORE THAN 0.5 GALLONS PER FLUSH, BOTH FLUSHOMETERS ABOVE SHALL MEET PERFORMANCE STANDARDS BY ANSI A112.19.2 H45 CODE, SECTION 17921.3(B), SINK FAUCET SHALL USE NO MORE THAN 1.8 GPM MEASURED AT 60 PSI.
- 10. WHEN FIXTURES REQUIRE WALL CARRIERS, THEY SHALL BE SUPPLIED BY CONTRACTOR.
- 11. NON-REMOVABLE BACKFLOW PREVENTION DEVICE SHALL BE INSTALLED ON ALL HOSE BIBBS AND POTABLE WATER OUTLETS WITH HOSE ATTACHMENTS. CPC 603.5.7.
- 12.UNLESS SPECIFIED IN THE ROMTEC SUBMITTAL, ROMTEC DOES NOT SUPPLY INSULATION OR "FREEZE" PROTECTION" FOR PLUMBING. "THE OWNER MAY NEED TO MINTERIZE THEIR BUILDING."

TOTAL

TOTAL

Ductwork, and Electrical Distribution System Bracing Note with the forces and displacements prescribed in ASCE 7—16 Section 3.3 as defined in ASCE 7-16 Sections 13.6.5, 13.6.6, 13.6.7, 13.6.8; and 2022 CBC, Sections 1617A.1.24, 1617A.1.25 and 1617A.1.26. The method of showing bracing and attachments to the structure for the identified distribution system are as noted below. When bracing and attachments are based on a preapproved installation guide (e.g., HCAi OPM for 2013 CBC or later), copies of the bracing system installation guide or manual shall be available on the jobsite prior to the start of and during the hanging and bracing of the distribution systems. The Structural Engineer of Record shall verify the adequacy of the structure to support the hanger and brace loads.

16.5

Mechanical Piping (MP), Mechanical Ducts (MD), Plumbing Piping (PP), Electrical Distribution Systems (E):

MP MD PP E E Option 1: Detailed on the approved drawings with

project specific notes and details. MP MD PP E Option 2: Shall comply with HCAi (OSHPD)

Preapproval (OPM #) #\_\_\_\_\_\_ as included in these drawings with

project-specific notes and details.

REFER TO SHEET S8.5 FOR STRUCTURAL DETAILS ON INSTALLING PLUMBING FIXTURES - WATERCLOSET, LAYATORY, DRINKING FOUNTAINS &

\*NOTE: INSTANT WATER HEATER.

LAN SET# MESO1 11/01/2023 REVISIONS 0 H RHW 0AHE BW 5 03 14 2024 CR

Applicable Code: 2022 CBC MEP Component Anchorage Note

All mechanical, plumbing, and electrical components shall be anchored and installed per the details on the DSA-approved construction documents. The following components shall be anchored or braced to meet the force and displacement requirements prescribed in the 2022 CBC Sections 1617A.1.18 through 1617A.1.26 and ASCE 7-16 Chapters 13, 26, and 30:

All permanent equipment and components.

2. Temporary, movable or mobile equipment that is permanently attached (e.g., hard wired) to the building utility services such as electricity, gas or water. Permanently attached shall include all electrical connections except plugs for 110/220 volt receptacles having a flexible cable.

3. Temporary, movable or mobile equipment which is heavier than 400 pounds or has a center of mass located 4 feet or more above the adjacent floor or roof level that directly support the component is required to be restrained in a manner approved by DSA.


The following mechanical and electrical components shall be positively attached to the structure but need not demonstrate design compliance with the references noted above. These components shall have flexible connections provided between the component and associated ductwork, piping, and conduit. Flexible connections must allow movement in both transverse and longitudinal directions:

A. Components weighing less than 400 pounds and having a center of mass located 4 feet or less above the adjacent floor or roof level that directly support the component. Components weighing less than 20 pounds, or in the case of distributed systems, less than 5 pounds per foot, which are suspended from a roof or floor or hung from a wall.

The anchorage of all mechanical, electrical and plumbing components shall be subject to the approval of the design professional in general responsible charge or structural engineer delegated responsibility and acceptance by DSA. The project inspector will verify that all components and equipment have been anchored in accordance with the above regulrements.

DRAWN BY

SHEET NO.



### MINIMUM VENTILATION RATES:

PUBLIC SPACES

1 CFM - PER SQ.FT

TO LET ROOMS (PER NC OR UR) EXHAUST AIRFLOW RATE 70 CFM - OPERATES INTERMITTENTLY MECH ROOM (62 FT²) EXHAUST AIRFLOW RATE

MECHANICAL EXHAUST SYSTEM SHALL BE INSTALLED PER INSTALL NSTRUCTIONS & DETAILS IN THE:

### "FINAL"

ROMTEC SCOPE OF SUPPLY AND DESIGN SUBMITTAL


### NOTE

REFER TO INTERIOR ELEVATIONS ON SHEET A1.4 FOR LOCATIONS OF WALL VENT REGISTERS.

EF INLINE FAN (2 lbs.) TO EXHAUST MECH IS LOCATED WITHIN THE SAME SPACE AND IS CONTROLLED 3 BY THE SWITCH NEXT TO THE



- 1. EXHAUST FANS AND ALL DUCTING TO BE MOUNTED USING DUCT HANGERS (SMIVEL HEAD SCREM HANGER) 3/8" THREADED ROD, ROUND STRAP BRACKET & GALY. DURO STRAP 1" - 22GA) OR EQUIVALENT PER DIRECTIONS FURNISHED BY MANUFACTURE, IN ACCORDANCE WITH THE MECHANICAL CODE AND SMACNA STANDARDS.
- 2. ALL DUCTMORK: RIGID DUCT W/ R8.3 INSULATED WRAP (UL LISTED CLASS 1 AIR DUCT). PROVIDE SHEETMETAL FITTINGS AT MAIN DUCT RUNOUTS AND CONNECTIONS WITH A MINIMUM OF THREE SHEETMETAL SCREWS AND TAPED TO PROVIDE AN AIRTIGHT SEAL. SUPPORT FLEX AS DIRECTED BY MANUFACTURER, NOT TO EXCEED 4'-0".
- THE DUCT DISCHARGES THRU A ROOF CAP W DAMPER, SCREEN AND COLLAR.
- 4. FANS ARE CONTROLLED BY OCCUPANCY SENSORS LOCATED IN EACH RESTROOM.
- 5. FAN IN MECH ROOM IS CONTROLLED BY A SMITCH.



Piping, Ductwork, and Electrical Distribution System Bracing Note iping, ductwork, and electrical distribution systems shall be braced to comply with the forces and displacements prescribed in ASCE 7-16 Section 13.3 as defined in ASCE 7-16 Sections 13.6.5, 13.6.6, 13.6.7, 13.6.8; and 2022 CBC, Sections 1617A.1.24, 1617A.1.25 and 1617A.1.26. The method of showing bracing and attachments to the structure for the identified distribution system are as noted below. When bracing and attachments are based on a preapproved installation guide (e.g., HCAI OPM for 2013 CBC or later), copies of the bracing system installation guide or manual shall be available on the jobsite prior to the start of and during the hanging and bracing of the distribution systems. The Structural Engineer of Record shall verify the adequacy of the structure to support the hanger and brace loads. Mechanical Piping (MP), Mechanical Ducts (MD), Plumbing Piping (PP), Electrical Distribution Systems (E): MP□ MD▼ PP□ E□ Option 1: Detailed on the approved drawings with project specific notes and details. MP MD PP E□ Option 2: Shall comply with HCAi (OSHPD) \_\_\_ as included in these drawings with Preapproval (OPM #) #\_ project-specific notes and details.

DOOR, TYP. 5-0 10-8" 3-4 EXHAUST FAN ROOF CAP W 6" COLLAR & BIRD SCREEN. SEAL PENETRATION W/ METAL MECH ROOF VENT SEALING ADAPTER MULTI-FLASH, DUCT HANGER, TYP. (5) BACKDRAFT/ BUTTERFLY DAMPER @ EACH REGISTER, TYP.(3) ALL-GENDER ALL-GENDER ADA RESTROOM ADA RESTROOM 36 GAL

EF INLINE FAN (2 lbs.) TO EXHAUST EACH RESTROOM IS LOCATED IN MECH ROOM AND IS CONTROLLED BY OCCUPANCY SENSOR IN EACH RESTROOM, TYP. (2)

Applicable Code: 2022 CBC MEP Component Anchorage Note

All mechanical, plumbing, and electrical components shall be anchored and installed per the details on the DSA-approved construction documents. The following components shall be anchored or braced to meet the force and displacement requirements prescribed in the 2022 CBC Sections 1617A.1.18 through 1617A.1.26 and ASCE 7-16 Chapters 13, 26, and 30: All permanent equipment and components.

Temporary, movable or mobile equipment that is permanently attached (e.g., hard wired) to the building utility services such as electricity, gas or water. Permanently attached shall include all electrical connections except plugs for 110/220 volt receptacles having a flexible cable.


Temporary, movable or mobile equipment which is heavier than 400 pounds or has a center of mass located 4 feet or more above the adjacent floor or roof level that directly support the component is required to be restrained in a manner approved by DSA. The following mechanical and electrical components shall be positively attached to the structure but need not demonstrate design compliance with the references noted above. These components shall have

flexible connections provided between the component and associated ductwork, piping, and conduit. Flexible connections must allow movement in both transverse and longitudinal directions: A. Components weighing less than 400 pounds and having a center of mass located 4 feet or less

above the adjacent floor or roof level that directly support the component. Components weighing less than 20 pounds, or in the case of distributed systems, less than 5 pounds per foot, which are suspended from a roof or floor or hung from a wall.

The anchorage of all mechanical, electrical and plumbing components shall be subject to the approval of the design professional in general responsible charge or structural engineer delegated responsibility and acceptance by DSA. The project inspector will verify that all components and equipment have been anchored in accordance with the above requirements.

MECHANICAL PLAN




**PLAN SET#** MESO1

11/01/2023 REVISIONS


# GENERAL ELECTRICAL NOTES:

- ALL WORK SHALL COMPLY WITH 2022 CALIFORNIA ELECTRICAL CODE AND LOCAL CODES.
- 2. ONNER TO PROVIDE TEMPORARY POMER AS REQUIRED DURING COURSE OF CONSTRUCTION.
- 3. ELECTRICAL SERVICE EQUIPMENT SUPPLIED BY OTHERS UNDER SEPARATE SUBMITTAL
- 4. THE AIC VALUES SHOWN ON THESE ROMTEC PLANS ARE TO BE MADE CLEARLY AVAILABLE TO THE ELECTRICAL ENGINEER OF RECORD THAT WILL DESIGN THE MAIN SERVICE.
- 5. THE INSTALLER SHALL FURNISH & INSTALL SPECIFICATION GRADE CIRCUIT BREAKERS, MIRING, CONDUIT, SMITCHES AND GFI RECEPTACLES THROUGHOUT. INTERIOR RECEPTACLES \$ SMITCHES SHALL HAVE STAINLESS STEEL COVERPLATES AND EXTERIOR RECEPTACLES SHALL BE INSTALLED WITH A MEATHERPROOF IN USE COVER.
- 6. ELECTRICAL CONDUIT IS TO BE RUN WITHIN THE WALL WHEN POSSIBLE, EXCEPT IN THE MECHANICAL ROOM.
- 7. FOR MECHANICAL ROOM ALL EXPOSED CONDUIT IS TO BE SURFACE MOUNTED AND RUN TIGHT TO CEILING AS REQUIRED.
- 8. COORDINATE AC OUTLET HEIGHTS WITH OWNER PRIOR TO ROUGH-IN.

# ELECTRICAL SCHEDULE & SYMBOL LEGEND:



S&P. TD-100 - 4": (26M) (0.22A)



Pipina, Ductwork, and Electrical Distribution System Bracing Note Piping, ductwork, and electrical distribution systems shall be braced to comply with the forces and displacements prescribed in ASCE 7-16 Section 13.3 as defined in ASCE 7-16 Sections 13.6.5, 13.6.6, 13.6.7, 13.6.8; and 2022 CBC, Sections 1617A.1.24, 1617A.1.25 and 1617A.1.26. The method of showing bracing and attachments to the structure for the identified distribution system are as noted below. When bracing and attachments are based on a preapproved installation guide (e.g., HCAi OPM for 2013 CBC or later), copies of the bracing system installation guide or manual shall be available on the jobsite prior to the start of and during the hanging and bracing of the distribution systems. The Structural Engineer of Record shall verify the adequacy of the structure to support the hanger and brace loads. | Mechanical Piping (MP), Mechanical Ducts (MD), Plumbing Piping (PP), Electrical Distribution Systems (E): MP $\square$  MD $\square$  PP $\square$  Elacktriangle Option 1: Detailed on the approved drawings with project specific notes and details.——  $|\mathsf{MP} \square \mathsf{MD} \square \mathsf{PP} \square \mathsf{E} \square \mathsf{Option} \mathsf{2}$ : Shall comply with HCAi (OSHPD) Preapproval (OPM #) #\_\_\_\_\_, as included in these drawings with

project-specific notes and details.

MEP Component Anchorage Note

1617A.1.26 and ASCE 7-16 Chapters 13, 26, and 30:

All permanent equipment and components.

Applicable Code: 2022 CBC

NOTE:

REFER TO SHEET S8.5 FOR STRUCTURAL DETAILS ON INSTALLING ELECTRICAL EQUIPMENT AS NOTED PER SCHEDULE.

WESO1 11/01/2023 **REVISIONS** 3 02-15-2024 5 03-14-2024

 $\vec{\Omega}$ 

the DSA—approved construction documents. The following components shall be anchored or braced to meet the force and displacement requirements prescribed in the 2022 CBC Sections 1617A.1.18 through Temporary, movable or mobile equipment that is permanently attached (e.g., hard wired) to the

building utility services such as electricity, gas or water. "Permanently attached" shall include all electrical connections except plugs for 110/220 volt receptacles having a flexible cable. Temporary, movable or mobile equipment which is heavier than 400 pounds or has a center of

All mechanical, plumbing, and electrical components shall be anchored and installed per the details on

mass located 4 feet or more above the adjacent floor or roof level that directly support the component is required to be restrained in a manner approved by DSA.

The following mechanical and electrical components shall be positively attached to the structure but need not demonstrate design compliance with the references noted above. These components shall have flexible connections provided between the component and associated ductwork, piping, and conduit. Flexible connections must allow movement in both transverse and longitudinal directions: A. Components weighing less than 400 pounds and having a center of mass located 4 feet or less

above the adjacent floor or roof level that directly support the component. B. Components weighing less than 20 pounds, or in the case of distributed systems, less than 5 pounds per foot, which are suspended from a roof or floor or hung from a wall.

The anchorage of all mechanical, electrical and plumbing components shall be subject to the approval of the design professional in general responsible charge or structural engineer delegated responsibility and acceptance by DSA. The project inspector will verify that all components and equipment have been




NOTE: SEE SHEETS A1.4, A2.1, & A2.2 FOR LOCATIONS - HEIGHTS OF ELECTRICAL FIXTURES.

NOTE: ELECTRICAL PANEL MAY BE RELOCATED AT THE DISCRETION OF THE INSTALLER, PANEL MUST MAINTAIN ALL APPLICABLE CODE CLEARANCES.




ROMTEC HAS DESIGNED THIS ELECTRICAL SYSTEM TO MEET THE NEEDS OF THIS SPECIFIC FACILITY. SITE DESIGN AND ENGINEERING BY OTHERS. OWNER IS RESPONSIBLE TO PROVIDE ALL SERVICE AND/OR UTILITY ENTRANCE DESIGN. FIELD VERIFY THAT SERVICE CONDUCTOR SIZE IS ADEQUATE FOR VOLTAGE DROP. ANY ADDITIONAL POWER OR LIGHTING LOADS NOT SHOWN ON THESE PLANS SHALL BE ENGINEERED BY OTHERS.





ELECTRICAL PLAN

SCALE: 1/4" = 1'-0"



WESO1 11/01/2023 **REVISIONS** 3 02-15-2024 CF





								BR	EAK	ER	PA	NEL						25k AIC F	RAT	ING
20	00	AMP	M	AIN B	REAKE	ER		12	20 ,	/ 24	10	VOLT	5					1-PHASE, 3	3-M	IRE
F	EED	ER SIZE:	Al	_UM: 3	3 #250	PH, #	4 GRI	D, 2"	C									SURFACE MO	NUN-	ΓED
E	_EC	TRICAL MIRING:	G	ROUNI	DED &	BONI	PER	- CE	C				USE X	HHM-2	CU CC	DNDUC	TORS			
LC	AD [	PISTRIBUTION	LTG	REC	MOTOR	DATA	HEAT	MISC					PH-A	PH-B	=	TOTAL	AMPS	MITH SPAR	XE	25%
	NNEC	CTED VA	4978	195	0	0	11330	0					6996	9506	=	16503	79	20628		99
	/ERS	ITY FACTOR	125%	100%	100%	100%	100%	100%							=					
DI	/ERS	IFIED VA	6222	195	0	0	11330	0					7326	10422	=	17747	87	22184		108
PL	Т	LOAD	VA	HP	PHW	GND	CON	BKR		PH		BKR	CON	GND	PHW	HP	VA	LOAD	Т	PL
1_	Н	WATER HEATER	4750		8	10	3/4	50	2	Α	1	20	1/2	12	12		36	LTS: EXTERIOR	L	2
3	Н		4750							В	1	20	1/2	12	12		61	LTS: MECH	L	4
5	Н	HAND DRYER	915		12	12	1/2	20	1	Α	1	20	1/2	12	12		80	LTS: RESTROOMS	L	6
7	Н	HAND DRYER	915		12	12	1/2	20	1	В	1	20	1/2	12	12		1200	SECURITY LIGHTS	L	8
9	R	DRINKING FOUNTAIN	15		12	12	1/2	20	1	Α	1	20	1/2	12	12		1200	SECURITY LIGHTS	L	10
11	R	RECEPTACLE	180		12	12	1/2	20	1	В	1	30	1/2	10	10		2400	SECURITY LIGHTS	L	12
13										Α										14
15										В										16
17										Α										18
19										В										20
21										Α										22
23										В										24
25										Α										26
27										В										28
29										A										30

PLEASE NOTE THAT THE VALUES FOR THE SECURITY LIGHTS ARE AN ESTIMATE. SEE PROJECT ELECTRICAL ENGINEERING PLANS FOR FINAL LOADS.

1 ELECTRICAL PANEL SCHEDULE

SCALE: NONE

ROMTEC HAS DESIGNED THIS ELECTRICAL SYSTEM TO MEET THE NEEDS OF THIS SPECIFIC FACILITY. SITE DESIGN AND ENGINEERING BY OTHERS. OWNER IS RESPONSIBLE TO PROVIDE ALL SERVICE AND/OR UTILITY ENTRANCE DESIGN. FIELD VERIFY THAT SERVICE CONDUCTOR SIZE IS ADEQUATE FOR VOLTAGE DROP. ANY ADDITIONAL POWER OR LIGHTING LOADS NOT SHOWN ON THESE PLANS SHALL BE ENGINEERED BY OTHERS.

11/01/2023 REVISIONS 1 11-07-2023 CR 3 02-15-2024 CR



### **BUILDING ENERGY ANALYSIS REPORT**

### PROJECT:

2311-012 West Campus 5022 58th St, Sacramento, CA 95820

### Project Designer:

Double 'E' Engineering, LLC 315 Ash Street Myrtle Point, Oregon 97458 541-294-0587

### Report Prepared by:

Matthew Weldon Regerfour LLC dba 5 Star Energy 940 Merchant St. Redding, Ca 96002 530-275-3350

### Job Number:

2311-012

### Date:

2/28/2024

The EnergyPro computer program has been used to perform the calculations summarized in this compliance report. This program has approval and is authorized by the California Energy Commission for use with both the Residential and Nonresidential 2022 Building Energy Efficiency Standards.

This program developed by EnergySoft, LLC – www.energysoft.com.

### **TABLE OF CONTENTS**

Cover Page Table of Contents Form NRCC-LTI-E Indoor Lighting Form NRCC-LTO-E Outdoor Lighting 11/01/2023



Rated Power Reduction Compliance (See Table Q for Details)

STATE OF CALIFORNIA **Indoor Lighting** CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTI-E This document is used to demonstrate compliance with requirements in 110.9, 110.12(c), 130.0, 130.1, 140.6 and 141.0(b)2 for indoor lighting scopes using the prescriptive path for nonresidential and hotel/motel occupancies. It is also used to document compliance with requirements in 160.5, 170.2(e) and 180.2(b)4 for indoor lighting scopes using the prescriptive path for multifamily occupancies. Multifamily includes dormitory and senior living facilities. Project Name: 2311-012 West Campus (Page 1 of 7) Report Page: 5022 58th St, Date Prepared: 2/28/2024 Project Address:

A. GENERAL INFORMATION								
01 Project Location (city)	Sacramento	04	Total Conditioned Floor Area (ft²)	0				
02 Climate Zone	12	05	Total Unconditioned Floor Area (ft²)	222				
03 Occupancy Types Within Project (	select all that apply):	06	# of Stories (Habitable Above Grade)	1				
• Support Areas								

### **B. PROJECT SCOPE**

This table includes any lighting systems that are within the scope of the permit application and are demonstrating compliance using the prescriptive path outlined in 140.6 / 170.2(e) or 141.0(b)2 / 180.2(b)4 for alterations.

Scope of Work	Conditioned Space	es	Unconditioned Spaces		
01	02	03	04	05	
My Project Consists of (check all that apply):	Calculation Method	Area (ft²)	Calculation Method	Area (ft <sup>2</sup> )	
□ New Lighting System	Area Category Method	0	Area Category Method	222	
☐ New Lighting System - Parking Garage					
Total Area of Work (ft²)	0	222			

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000 Schema Version: rev 20220101 Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58 STATE OF CALIFORNIA

**Indoor Lighting** CALIFORNIA ENERGY COMMISSION **CERTIFICATE OF COMPLIANCE** NRCC-LTI-E Report Page: Project Name: 2311-012 West Campus (Page 2 of 7) Date Prepared: 2/28/2024

g any cen on ans tabl		X	or "COMPLIES ( Power per 140.	•			r to	, ,	1	140	.6(a) / 170.2(e)	Compliance Results
Lighting in conditioned and unconditioned spaces must not be combined for compliance per 140.6(b)1 / 170.2(e)	01	02	03	04	05		06	07	08		09	
	Complete Building 140.6(c)1	Area Category 140.6(c)2 / 170.2(e)4	Area Category Additional 140.6(c)2G / 170.2(e)4Av (+)	Tailored 140.6(c)3 / 170.2(e)4B (+)	=	<b>Total Allowed</b> (Watts)	>	Total Designed (Watts)	Adjustments PAF Lighting Control Credits 140.6(a)2 / 170.2(e)1B (-)	ш	Total Adjusted (Watts) *Includes Adjustments	05 must be >= 08 140.6 / 170.2(e)
	(See Table I)	(See Table I)	(See Table J)	(See Table K)				(See Table F)	(See Table P)			
Conditioned					=		≥			=		
Unconditioned		144.3	0		=	144	≥	63	0	=	63	COMPLIES
							J	Contro	ls Compliance (	See '	Table H for Details	COMPLIES

D. EXCEPTIONAL CONDITIONS

This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Generated Date/Time:


Report Version: 2022.0.000

Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58

MESO1 11/01/2023 **REVISIONS** 



STATE OF CALIFORNIA

Indoor Lighting CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTI-E Report Page: **Project Name:** 2311-012 West Campus (Page 3 of 7) Date Prepared: 2/28/2024

#### F. INDOOR LIGHTING FIXTURE SCHEDULE

This table includes all planned permanent and portable lighting other than dwelling unit/hotel/motel room lighting. Multifamily dwelling unit and hotel/motel room lighting is documented in Table T. If using Table T to document lighting in multifamily common use areas providing shared provisions for living, eating, cooking or sanitation, those luminaires are not included here.

#### Designed Wattage: Unconditioned Spaces

Designed wat	Designed Wattage: Officialitioned Spaces										
01	02	03	04	05	06	07	08	09	1	0	
Name or Item	Complete Luminaire	Modular	Small	Watts per	How is Wattage	Total Number	Excluded per		Field In:	spector	
Tag	Description	(Track) Fixture	Aperture & Color Change <sup>1</sup>	luminaire <sup>2</sup>		of Luminaires	140.6(a)3 / 170.2(e)2C	Design Watts	Pass	Fail	
LF-2	Lithonia OLLWD LED 14w (LF-2)	No	NA	14	Mfr. Spec	2	No	28			
LF-3	Lithonia 48" Vapor Tight Wall Mount 35.3w LED	No	NA	35.3	Mfr. Spec	1	No	35.3			
	Total Designed Watts: UNCONDITIONED SPACE										

<sup>1</sup>FOOTNOTE: Design Watts for small aperture and color changing luminaires which qualify per 140.6(a)4B / 170.2(e)2D is adjusted to be 75% /80% of their rated wattage. Table F automatically makes this adjustment, the permit applicant should enter full rated wattage in column 05.

<sup>2</sup>Authority Having Jurisdiction may ask for Luminaire cut sheets to confirm wattage used for compliance per 130.0(c) / 160.5(b). Wattage used must be the maximum rated for the luminaire, not the lamp.

### G. MODULAR LIGHTING SYSTEMS

This section does not apply to this project.

#### H. INDOOR LIGHTING CONTROLS (Not including PAFs)

This table includes lighting controls for conditioned and unconditioned spaces.

Building Level Controls			
01	02	0	3
Mandatory Demand Response 110.12(c)	Shut-off controls 130.1(c) / 160.5(b)4C	Field In	spector
ivialidatory Demand Response 110.12(c)	311ut-011 controls 130.1(c) / 160.3(b)4C	Pass	Fail
NA < 4,000W subject to multilevel	See Area/Space Level Controls		

Generated Date/Time:

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000 Schema Version: rev 20220101 Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58 STATE OF CALIFORNIA

**Indoor Lighting** 

CALIFORNIA ENERGY COMMISSION

NRCC-LTI-E

CERTIFICATE OF COMPLIANCE

**Project Name:** 2311-012 West Campus

Report Page:

(Page 4 of 7) Date Prepared: 2/28/2024

H. INDOOR LIGHTING CONTROLS (Not including PAFs)

		06	07	08	09	10	11	1	2
Area Description	Complete Building or Area Category Primary Function Area	Manual Area Controls 130.1(a) / 160.5(b)4A	Multi-Level Controls 130.1(b) / 160.5(b)4B	Shut-Off Controls 130.1(c) // 160.5(b)4C	Primary/Sky lit Daylighting 130.1(d) / 160.5(b)4D	Secondary Daylighting 130.1(d)/ 160.5(b)4D	Interlocked Systems 140.6(a)1/ 170.2(e)2A	Field In Pass	spector Fail
Whole Building	All Other Space Types	Readily Accessible	Dimmer	See Building Level	Included	Included	No		

I. LIGHTING POWER ALLOWANCE: COMPLETE BUILDING OR AREA CATEGORY METHODS

Each area complying using the Complete Building or Area Category Methods per 140.6(b) are included in this table. Column 06 indicates if additional lighting power allowances per 140.6(c) or adjustments per 140.6(a) are being used .

nditioned Spaces

Unconditioned Spaces							
01	02	03	04	05	0	6	
Area Description	Complete Building or Area Category Primary	Allowed Density	Area (ft²)	Allowed Wattage	Additional Allowance / Adjustmen		
Area Description	Function Area	(W/ft²)	Alea (It )	(Watts)	Area Category	PAF	
Restrooms/Mech Storage	Restroom	0.65	222	144.3	No	No	
		TOTALS:	222	144.3	See Tables J, o	or P for detail	

J. ADDITIONAL ALLOWANCE: AREA CATEGORY METHOD QUALIFYING LIGHTING SYSTEM

This section does not apply to this project.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Documentation Software: EnergyPro


Report Version: 2022.0.000 Schema Version: rev 20220101

Generated Date/Time:

Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58

WESO1

11/01/2023 REVISIONS



STATE OF CALIFORNIA Indoor Lighting CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTI-E Report Page: (Page 5 of 7) **Project Name:** 2311-012 West Campus Date Prepared: 2/28/2024 K. TAILORED METHOD GENERAL LIGHTING POWER ALLOWANCE This section does not apply to this project. L. ADDITIONAL LIGHTING ALLOWANCE: TAILORED WALL DISPLAY This section does not apply to this project. M. ADDITIONAL LIGHTING ALLOWANCE: TAILORED FLOOR AND TASK LIGHTING This section does not apply to this project. N. ADDITIONAL LIGHTING ALLOWANCE: TAILORED DECORATIVE /SPECIAL EFFECTS This section does not apply to this project. O. ADDITIONAL LIGHTING ALLOWANCE: TAILORED VERY VALUABLE MERCHANDISE This section does not apply to this project. P. POWER ADJUSTMENT: LIGHTING CONTROL CREDIT (POWER ADJUSTMENT FACTOR (PAF)) This section does not apply to this project. Q. RATED POWER REDUCTION COMPLIANCE FOR ONE-FOR-ONE ALTERATIONS This section does not apply to this project.

Generated Date/Time:

Report Version: 2022.0.000

Schema Version: rev 20220101

R. 80% LIGHTING POWER FOR ALL ALTERATIONS - CONTROLS EXCEPTIONS

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

This section does not apply to this project.

STATE OF CALIFORNIA Indoor Lighting CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE Report Page: **Project Name:** 2311-012 West Campus Date Prepared: S. DAYLIGHT DESIGN POWER ADJUSTMENT FACTOR (PAF) This section does not apply to this project. T. DWELLING UNIT LIGHTING This section does not apply to this project. U. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION Selections have been made based on information provided in this document. If any selections have been changed by permit applicant, an explanation should be included in Table E. Additional Remarks. These documents must be provided to the building inspector during construction and can be found online Form/Title

NRCI-LTI-E - Must be submitted for all buildings

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Documentation Software: EnergyPro

Compliance ID: EnergyPro-3895-0224-1692

Report Generated: 2024-02-28 15:17:58

V. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE Selections have been made based on information provided in this document. If any selections have been changed by the permit applicant, an explanation should be included in Table E. Additional Remarks. These documents must be provided to the building inspector during construction and any with "-A" in the form name must be completed through an Acceptance Test Technician Certification Provider (ATTCP). For more information visit: http://www.energy.ca.gov/title24/attcp/providers.html

Systems/Spaces To Be Field Form/Title Verified Whole Building; NRCA-LTI-03-A - Must be submitted for automatic daylight controls.

> Generated Date/Time: Documentation Software: EnergyPro Report Version: 2022.0.000 Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58 Schema Version: rev 20220101

NRCC-LTI-E

(Page 6 of 7)

2/28/2024

11/01/2023

WESO1

REVISIONS



STATE OF CALIFORNIA			STATE OF CALIFORNIA			
Indoor Lighting		CALIFORNIA ENERGY COMMISSION	Outdoor Lighting		CALIFORNIA ENERGY COMMISSION	
CERTIFICATE OF COMPLIANCE		NRCC-LTI-E	CERTIFICATE OF COMPLIANCE		NRCC-LTO-E	
Project Name: 2311-012 West Campus	Report Page:	(Page 7 of 7)	This document is used to demonstrate compliance with requirements in 110	.9, 130.0, 130.2, 140.7, and 141.0(b)2L for outdoor l		
Project Address:	5022 58th St, Date Prepared:	2/28/2024	nonresidential and hotel/motel occupancies. It is also used to document con			
<u> </u>			the prescriptive path for multifamily and mixed-use occupancies. Multifamil	y includes dormitory and senior living facilities.		
			Project Name: 2311-012 West Campus	Report Page:	(Page 1 of 7)	
DOCUMENTATION AUTHOR'S DECLARATION STATEMENT			Project Address:	5022 58th St, Date Prepared:	2/28/2024	$\sim$
I certify that this Certificate of Compliance documentation is accura	ate and complete.					LE E ITE E
Documentation Author Name:	Documentation Author Signature:		A. GENERAL INFORMATION			J Soin Poin Poin Poin Poin Poin Poin Poin P
Matthew Weldon	Matthew Weldon		01 Project Location (city) Sacramento			
Company:	Signature Date:		02 Climate Zone 12	O4 Total Illuminated Hardscape A	Area (ft <sup>2</sup> ) 540	
Regerfour LLC dba 5 Star Energy	2024-02-28		03 Outdoor Lighting Zone per Title 24 Part 1 10.114 or as designated by A	uthority Having Jurisdiction (AHI)·		
Address: 940 Merchant St.	CEA/ HERS Certification Identification (if app	olicable):	□ LZ-0: Very Low - Undeveloped Parkland □ LZ-2: Moderate - Urban		d by CA Energy Commission for Approval	
City/State/Zip:	Phone:		□ LZ-1: Low - Rural Areas □ LZ-3: Moderate - Orban	-	d by CA Lifetgy Commission for Approval	
Redding Ca 96002	530-275-3350			Orban Areas		
RESPONSIBLE PERSON'S DECLARATION STATEMENT	<b>.</b>		05 Occupancy Types within Project			
I certify the following under penalty of perjury, under the laws of the State of California:			Support Areas			P =   C
1. The information provided on this Certificate of Compliance is true and correct.	anathillan fangles beetleke skriver	Contillanta of Consultance (new control of the cont				\( \times \)   \( \times \)
<ol> <li>I am eligible under Division 3 of the Business and Professions Code to accept responses.</li> <li>The energy features and performance specifications, materials, components, and in</li> </ol>			D. DDOJECT CCODE			\(\frac{1}{2} \)
of Title 24, Part 1 and Part 6 of the California Code of Regulations.			B. PROJECT SCOPE			Σ 💆
<ol> <li>The building design features or system design features identified on this Certificate plans and specifications submitted to the enforcement agency for approval with the</li> </ol>		other applicable compliance documents, worksheets, calculations,	This table includes outdoor lighting systems that are within the scope of the	permit application and are demonstrating complian	nce using the prescriptive path outlined in 140.7/	
5. I will ensure that a completed signed copy of this Certificate of Compliance shall be	e made available with the building permit(s) issued for the building		170.2(e)6 or 141.0(b)2L / 180.2(b)4Bv for alterations.			<u>                                    </u>
inspections. I understand that a completed signed copy of this Certificate of Comp		der provides to the building owner at occupancy.	My Project Consists of:			\frac{1}{2} \frac{1}{2}
Responsible Designer Name:  Greg Pride	Responsible Designer Signature:		01	02		
Company:	Date Signed:		✓   New Lighting System   Must Comply	with Allowances from 140.7 / 170.2(e)6		
Double 'E' Engineering, LLC	2024-02-28		☐ Altered Lighting System Is your alterat	ion increasing the connected lighting load (Watts)?	Yes No	
Address:	License:		03	04	05	4 <u>2</u>   5   7   4   4   4   4
315 Ash Street	E19431		% of Existing Luminaires Being Altered <sup>1</sup> Sum	Total of Luminaires Being Added or Altered	Calculation Method	\$\disp\{\infty} \  \forall \forall \  \forall \  \forall \  \forall \  \forall \  \forall \forall \  \forall \forall \  \forall \  \forall \  \forall \  \forall \forall \  \forall \  \f
City/State/Zip: Myrtle Point OR 97458	Phone: 541-294-0587		□ < 10% □ >= 10% and < 50% □ >= 50%			
Wiyi de Folite Oit 37430	3-11 23-1 0307		Please proceed to Table F. Outdoor Lighting Fixture Schedule to define the	project's luminaires.		
			<sup>1</sup> FOOTNOTES: % of Existing Luminaires Being Altered = (Sum Total of Lumina)	aires Being Added or Altered / Existing Luminaires w	vithin the Scope of the Permit Application) x 100.	
						1 世 3 <b> </b> 2 <b>  3</b>   6 世   1
						$ \ddot{v}, \ddot{\delta}   \ddot{S}   \ddot{O}   O   A $
	Generated Date/Time:	Documentation Software: EnergyPro		Generated Date/Time:	Documentation Software: EnergyPro	
	Generated Date/Time:	Documentation Software: EnergyPro		Generated Date/Time:	Documentation Software: EnergyPro	
CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000	Compliance ID: EnergyPro-3895-0224-1692	CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance	Report Version: 2022.0.000	Compliance ID: EnergyPro-3895-0224-1692	$  \mathcal{V} \times \Sigma   \mathcal{V} \cap \mathcal{V}  $
	Schema Version: rev 20220101	Report Generated: 2024-02-28 15:17:58		Schema Version: rev 20220101	Report Generated: 2024-02-28 15:17:58	
						立 当 [kg <b>マ</b> の [
						PLAN SET# NESO
						Z Z DATE:
						11/01/20
						EVISION REVISION
						И Н REV. DATE: 4 02-27-2024
						¥ B
						Ä F I



STATE OF CALIFORNIA **Outdoor Lighting** CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTO-E Report Page: (Page 2 of 7) **Project Name:** 2311-012 West Campus Date Prepared: 2/28/2024

Results in this table are automatically calculated from data input and calculations in Tables F through N. Note: If any cell on this table says "COMPLIES with Exceptional Conditions" refer to Table D. Exceptional Conditions for guidance or see applicable Table referenced below. Calculations of Total Allowed Lighting Power (Watts) 140.7 / 170.2(e)6 or 141.0(b)2L / 180.2(b)4Bv **Compliance Results** General Existing Per Specific Per Ornamental Hardscape **Application** 140.7(d)2/ **Total Allowed Total Actual** Allowance Frontage Allowance 140.7(d)2/ 07 must be >= 08 140.7(d)2/ 140.7(d)1, 140.7(d)2 170.2(e)6 (Watts) 141.0(b)2L/ (Watts) 170.2(e)6 170.2(e)6 (See Table L) 180.2(b)4Bv 170.2(e)6 (See Table K) (See Table J) (See Table M) (See Table I (See Table N) 273 COMPLIES 273 36 **Shielding Compliance (See Table G for Details)** 

### D. EXCEPTIONAL CONDITIONS

C. COMPLIANCE RESULTS

This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

Controls Compliance (See Table H for Details)

#### E. ADDITIONAL REMARKS

This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

Generated Date/Time:

Documentation Software: EnergyPro

Not applicable

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000 Schema Version: rev 20220101 Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58 STATE OF CALIFORNIA

**Outdoor Lighting** 

CALIFORNIA ENERGY COMMISSION

NRCC-LTO-E

CERTIFICATE OF COMPLIANCE

Report Page: **Project Name:** 2311-012 West Campus

(Page 3 of 7) 2/28/2024 Date Prepared:

36

lumens

#### F. OUTDOOR LIGHTING FIXTURE SCHEDULE

For new or altered lighting systems demonstrating compliance with 140.7 / 170.2(e)6 all new luminaires being installed and any existing luminaires remaining or being moved within the spaces covered by the permit application are included in the Table below. For altered lighting systems using the Existing Power method per 141.0(b)2L only new luminaires being installed and replacement luminaires being installed as part of the project scope are included (ie, existing luminaires remaining or existing luminaires being moved are not included). Outdoor lighting attached to multifamily buildings and controlled from the inside of a dwelling unit are included in Table H. and are not included here. All other multifamily outdoor lighting is included here.

Designed Watt	Designed Wattage:										
01	02	03	04	05	06	07	08	09	1	0	
Name or Item Tag	Complete Luminaire Description	Watts per Iuminaire <sup>1, 2</sup>	How is Wattage determined	Total Number Luminaires <sup>2</sup>	Luminaire Status <sup>3</sup>	Excluded per 140.7(a) / 170.2(e)6A	Design Watts	Cutoff Req. > 6,200 initial lumen output 130.2(b) / 160.5(c)1 <sup>4</sup>	Fie Inspe Pass		
I F-1	Lithonia OLIWD LED 9w (LE-1) 🖂 Linear	9	Mfr Spec	4	New		36	NA: < 6200			

New

**Total Design Watts:** 

\* NOTES: Selections with a \* require a note in the space below explaining how compliance is achieved. EX: Luminaire is lighting a statue; EXCEPTION 2 to 130.2(b)

Lithonia OLLWD LED 9w (LF-1) ☐ Linear

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

<sup>1</sup>FOOTNOTES: Authority Having Jurisdiction may ask for Luminaire cut sheets to confirm wattage used for compliance per 130.0(c) / 160.5(b)

<sup>2</sup> For linear luminaires, wattage should be indicated as W/lf instead of Watts/luminaire. Total linear feet should be indicated in column 05 instead of number of luminaires.

<sup>3</sup> Select "New" for new luminaires in a new outdoor lighting project, or for added luminaires in an alteration. Select "Altered" for replacement luminaires in an alteration. Select "Existing to Remain" for existing luminaires within the project scope that are not being altered and are remaining. Select "Existing Reinstalled" for existing luminaires which are being removed and reinstalled as part of

Mfr. Spec

<sup>4</sup> Compliance with mandatory shielding requirements is required for luminaires with initial lumen output >= 6,200 unless exempted by 130.2(b)/ 160.5(c)

G. SHIELDING REQUIREMENTS (BUG)

This section does not apply to this project.

Generated Date/Time:

Report Version: 2022.0.000

Schema Version: rev 20220101

Documentation Software: EnergyPro

Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58

WESO1 11/01/2023 **REVISIONS** 



STATE OF CALIFORNIA		
Outdoor Lighting		CALIFORNIA ENERGY COMMISSION
CERTIFICATE OF COMPLIANCE		NRCC-LTO-
Project Name: 2311-012 West Campus	Report Page:	(Page 4 of 7
	Date Prepared:	2/28/202

#### H. OUTDOOR LIGHTING CONTROLS

This table demonstrates compliance with controls requirements for all new or altered luminaires installed as part of the permit application. For alteration projects, luminaires which are existing to remain (ie untouched) and luminaires which are removed and reinstalled (wiring only) do not need to be included in this table even if they are within the spaces covered by the permit application.

Outdoor lighting for nonresidential buildings, parking garages and common service areas in multifamily buildings must be documented separately from outdoor lighting attached to multifamily buildings and controlled from the inside of a dwelling unit

Mandatory Controls for Nonresidential Occupancies, Parking Garages & Common Areas in Multifamily Buildings

01	02	03	04	05		
Area Description	Shut-Off 130.2(c)1 / 160.5(c)	Auto-Schedule 130.2(c)2 / 160.5(c)	Motion Sensor 130.2(c)3 / 160.5(c)	Field Inspector		
				Pass	Fail	

<sup>&</sup>lt;sup>1</sup>FOOTNOTE: Text has been abbreviated, please refer to Table 160.5-A to confirm compliance with the specific light source technologies listed.

Generated	Date/Time

Documentation Software: EnergyPro

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

Report Version: 2022.0.000 Schema Version: rev 20220101 Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58

#### STATE OF CALIFORNIA

**Outdoor Lighting** CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTO-E Report Page: Project Name: 2311-012 West Campus (Page 5 of 7) Date Prepared: 2/28/2024

I. LIGHTING POWER ALLOWANCE (per 140.7 / 170	0.2(e))						
This table includes areas using allowance calculations per 140.7 / 170.2(e). General			01				
Hardscape Allowance is per Table 140.7-A/Table 170.2-			"Use it or lose it" Allowance (select all that apply) (select all that apply)				
Allowances are per Table 140.7-B /Table 170.2-S. Indicate which allowances are being used to expand sections for user input. Luminaires that qualify for one of the "Use it or lose it" allowances shall not qualify for another "Use it or lose it" allowance.  Outdoor lighting attached to multifamily buildings and controlled from the inside of a dwelling unit are included in Table H. and are not included here. All other multifamily outdoor lighting is included here.			☑ General Hardscape Allowance Table I (below)	☐ Per Application Table J	□ Sales Frontage Table K	☐ Ornamental Table L	☐ Per Specific Area Table M
Calculated General Hardscape Lighting Power Allowance per Table 140.7-A for Nonresidential & Hotel/Motel							
02	03	04	05	06	07	08	09
	Area Wattage Allowand		(AWA)	Linear Wattage Allowance (LWA)			Total General
Area Description	Illuminated Area (ft <sup>2</sup> )	Allowed Density (W/ft <sup>2</sup> )	Area Allowance (Watts)	Perimeter Leng (lf)	th Allowed Density (W/lf)	Linear Allowance (Watts)	AWA + LWA (Watts)
Entrances Side Walk	540	0.021	11.3	60	0.2	12	23
Initial Wattage Allowance for Entire Site (Watts):						250	
Instances of Initial Wattage Allowance (LZ 0 only) <sup>1</sup>							
Total General Hardscape Allowance (Watts):						273	

J.	LIGHTING ALLOWANCE: F	PER	APPLICATION

This section does not apply to this project.

### K. LIGHTING ALLOWANCE: SALES FRONTAGE

This section does not apply to this project.

#### L. LIGHTING ALLOWANCE: ORNAMENTAL

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance

This section does not apply to this project.

Generated Date/Time:

Documentation Software: EnergyPro


Report Version: 2022.0.000 Schema Version: rev 20220101

Compliance ID: EnergyPro-3895-0224-1692 Report Generated: 2024-02-28 15:17:58

WESO1 11/01/2023 **REVISIONS** 

<sup>&</sup>lt;sup>2</sup>Authority having jurisdiction may ask for cutsheets or other documentation to confirm compliance of light source.

<sup>&</sup>lt;sup>3</sup>Recessed luminaires marked for use in fire-rated installations, and recessed luminaires installed in non-insulated ceilings are excepted from ii and iii.



STATE OF CALIFORNIA STATE OF CALIFORNIA **Outdoor Lighting Outdoor Lighting** CALIFORNIA ENERGY COMMISSION CALIFORNIA ENERGY COMMISSION CERTIFICATE OF COMPLIANCE NRCC-LTO-E CERTIFICATE OF COMPLIANCE NRCC-LTO-E Report Page: Report Page: (Page 7 of 7) (Page 6 of 7) **Project Name:** 2311-012 West Campus **Project Name:** 2311-012 West Campus Date Prepared: 5022 58th St, Date Prepared: 2/28/2024 2/28/2024 Project Address: DOCUMENTATION AUTHOR'S DECLARATION STATEMENT M. LIGHTING ALLOWANCE: PER SPECIFIC AREA I certify that this Certificate of Compliance documentation is accurate and complete. This section does not apply to this project. Documentation Author Signature:
Walthew Weldon Documentation Author Name: Matthew Weldon N. EXISTING CONDITIONS POWER ALLOWANCE (alterations only) Regerfour LLC dba 5 Star Energy 2024-02-28 This section does not apply to this project. CEA/ HERS Certification Identification (if applicable): 940 Merchant St. City/State/Zip: 530-275-3350 O. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION Redding Ca 96002 RESPONSIBLE PERSON'S DECLARATION STATEMENT Selections have been made based on information provided in this document. If any selection has been changed by permit applicant, an explanation should be included in Table E. Additional Remarks. These documents must be provided to the building inspector during construction and can be found online I certify the following under penalty of perjury, under the laws of the State of California: 1. The information provided on this Certificate of Compliance is true and correct. Form/Title 2. I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer) The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements NRCI-LTO-E - Must be submitted for all buildings of Title 24, Part 1 and Part 6 of the California Code of Regulations. 4. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. I will ensure that a completed signed copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building, and made available to the enforcement agency for all applicable P. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE inspections. I understand that a completed signed copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy. Responsible Designer Signature: There are no NRCA forms required for this project. Responsible Designer Name: Greg Pride Double 'E' Engineering, LLC 2024-02-28 License: E19431 315 Ash Street City/State/Zip: Myrtle Point OR 97458 541-294-0587 Generated Date/Time: Documentation Software: EnergyPro Generated Date/Time: Documentation Software: EnergyPro Compliance ID: EnergyPro-3895-0224-1692 CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance Report Version: 2022.0.000 Compliance ID: EnergyPro-3895-0224-1692 CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance Report Version: 2022.0.000 Report Generated: 2024-02-28 15:17:58 Schema Version: rev 20220101 Report Generated: 2024-02-28 15:17:58 Schema Version: rev 20220101

WESO1

11/01/2023

**REVISIONS**